


Coarse Wave Division Multiplexers

Model 907-CWDM

Focal Technologies Corporation, a Moog Inc. company, has over 30 years of expertise in supplying standard and custom marine products for harsh environments and is a leading manufacturer of high performance and high quality multiplexers. Contact Focal for any assistance in selecting the best solution for your requirements.



The model 907 series of CWDMs combine multiple media converters or multiplexer motherboards onto a single fiber-optic cable. All CWDM cards are ITU-T G.694.2 compliant, passive (no electrical power required), and perform as both an optical multiplexer and optical de-multiplexer, allowing for bidirectional communication. They are form factor compatible with the 907 products and can be added to an existing stack, providing an upgrade path for additional functionality.

A 2-channel with a 1310/1550 nm bypass, 4-channel and 8-channel versions are available. The 2-channel version allows for simple expansion of an existing 1310/1550 nm Focal™ system.

Features

- Modular design
- Passive optics
- Compatible with all Model 907 products
- Available in 2-channel with bypass (907-CWDM), 4-channels (907-CWDM-4), or 8-channels (907-CWDM-8)
- Rugged design for harsh environments, including pressure tolerant version

Benefits

- Reduces the number of fibers required in cables and rotary joints
- Modular format allows for future upgrades and channel expansion

Applications

- Modular subsystems for Remote Operated Vehicles (ROVs)
- Multiple HD camera systems
- Imaging sonar systems
- Defense and security networks

Specifications

Optical	
Fiber Type	Singlemode (9/125 μm) Multimode (50/125 μm)
Center Wavelength	2-channel: 1310/1550, 1471, 1491 nm 4 channel: 1471, 1491, 1511, 1531 nm 8-channel: 1471, 1491, 1511, 1531, 1551, 1571, 1591, 1611 nm
Channel Spacing	20 nm
Isolation	> 30 dB
Return Loss	> 45 dB
Insertion loss	2-channel: < 2.5 dB 4 channel: < 2.5 dB 8-channel: < 3 dB
Options	Other wavelengths available, optional bypass port

Mechanical	
Dimensions	PC/104 (form-factor only) 3.550" x 3.775"
Weight	< 120 g (0.25 lb)
Options	Custom Enclosures, other form-factors available
Connectors	
Common	ST standard
To Cards	LC standard
Options	FC/PC
Environmental	
Temperature	0°C to +70°C (operational) -40°C to +85°C (storage)
Humidity	85% RH, non-condensing
Vibration	5 g, 25 - 1000 Hz, 3 axes
Shock	30 g, 11 ms, half-sine, 3 axes
Options	6000 psi pressure tolerant, extended temperature, stress screened or qualified

All specifications and information are subject to change without notice. Please contact Focal for the latest updates.

© 2017 Moog Inc. DS907-CWDM v1.0

www.moog.com/focal

Focal Technologies Corporation, A Moog Inc. Company